

The new STEYR MULTI series from 101hp to 117hp

ITS NAME SAYS IT **ALL**



Your partner to rely on.

STEYR
TRAKTOREN

A TRUE ALL-ROUNDER



Simple control with the Multicontroller armrest.



The very latest Stage V 4-cylinder 3.6 l Common Rail Turbodiesel engines with 101 to 117 hp.



The compact size and its 2.7 m total height allows perfect manoeuvrability even in the tightest areas.



ECOTRONIC – perfect matching of engine, transmission and operation.



Power Clutch for electronic clutch operation.



Reliable automated 32 x 32 transmission with 4-stage powershift transmission and electrohydraulic Powershuttle.




Thanks to its intelligent design, the MULTI cab offers perfect 360° visibility.



Low noise emission level (72 dB(A)) to take the stress out of working, and for using the telephone.



Eco mode – 40 kph at a fuel-efficient 1,730 rpm.



Automatic all-wheel drive and differential lock shift action.



4-stage PTO speeds with Power mode or fuel-efficient Eco mode.



Electronic hitch control (EHR) for precise adjustment of implements.



CCLS hydraulics with 80 l/min displacement, optional 100 l/min.



Electronic front hitch control (EFH) with implement strain relief for safe mowing on steep slopes.



Connections for attaching the front hitch.



Upgraded front axle suspension for improved traction and greater comfort.



Turning radius of just 4.30 metres, with a steering lock of 55 degrees.



S-TECH precision agricultural technology with ISOBUS II and Section Control.

THE **MULTITALENTED** AUSTRIAN





New Stage V engine

The new FPT F5 3.6 liters engine provides increased displacement, increased engine power and 5 % more torque compared to the previous models for better performance.



New after-treatment system

The unique HI-eSCR2 exhaust gas after-treatment system is perfectly integrated in a single and compact layout under the hood. It ensures an excellent operator visibility and vehicle manoeuvrability.



New electronic front hitch control offering

The new STEYR MULTI series are now available with Electronic front hitch control only without front PTO.



Enhanced visibility

We have added 2 rear low mounted worklights, for a total of 12 worklights providing superior visibility at night.

SPECIFICATIONS

MODEL	4100 MULTI	4110 MULTI	4120 MULTI	
TRANSMISSION				
S-Control™ 4 32 x32 automated 4-stage synchromesh transmission Driving speed* 0-40kph	●	●	●	
S-Control™ 4 with Pack-lock	●	●	●	
ENGINE				
FPT F5 3.6 l Common Rail Diesel engine, turbocharged and intercooled / HI-eSCR2 technology / Stage V Number of cylinders / Capacity [cm³]	4 / 3,600	4 / 3,600	4 / 3,600	
Max. engine power ECE R120 ¹⁾ [kW/hp]	74 / 101	81 / 110	86 / 117	
Rated engine power ECE R120 ¹⁾ [kW/hp]	74 / 101	81 / 110	86 / 117	
Engine speed at max. engine power [rpm]	1,900	2,300	1,900	
Rated engine speed [rpm]	2,300	2,300	2,300	
Max. torque [Nm @ 1,300rpm]	450	490	506	
Torque increase [%]	47	46	42	
Fuel tank Diesel / AdBlue* [l]	145 / 14	145 / 14	145 / 14	
PTO				
Electro-hydraulic PTO engagement	PTO speed [rpm] 540 / 540E / 1,000 / 1,000E	●	●	●
	Engine speeds [rpm] 1,805 / 1,542 / 1,880 / 1,606	●	●	●
	PTO shaft type	1 3/8" 21-splines / 1 3/8" 6-splines	1 3/8" 21-splines / 1 3/8" 6-splines	1 3/8" 21-splines / 1 3/8" 6-splines
	Ground speed PTO	●	●	●
	Front PTO* 1,000 @ 1,920 engine speed [rpm]	●	●	●
HYDRAULICS				
EHR Electronic hitch control	●	●	●	
Max. hydraulic pump capacity (CCLS) [l/min]	80 / 100	80 / 100	80 / 100	
Max. lift capacity / Lift capacity through range @ 610 mm [kg]	5,550 / 4,700	5,550 / 4,700	5,550 / 4,700	
Max. number of rear remote valves / mid mount valves	4 / 2	4 / 2	4 / 2	
Front-mounted hydraulics maximum lifting force [kg]	1,985	1,985	1,985	

MODEL		4100 MULTI	4110 MULTI	4120 MULTI
ALL-WHEEL DRIVE STEERING				
Steering angle [°]		55	55	55
Min. turning radius without breaks [m]		4.28	4.28	4.28
TYRES				
Maximum tyres ³⁾	Front	480/65 R24	480/65 R24	480/65 R24
	Rear	540/65 R38	540/65 R38	540/65 R38
WEIGHT				
Approximate shipping weight* [kg]		4,450	4,450	4,450
Permissible total weight [kg]		8,000	8,000	8,000
DIMENSIONS¹⁾				
Total length with front weight [mm]		4,403	4,403	4,403
Total width [mm]		2,100	2,100	2,100
Height from mid of rear axle to top of cab [mm]		1,925	1,925	1,925
Total height [mm]		2,740	2,740	2,740
Wheelbase standard / suspended axle [mm]		2,420 / 2,430	2,420 / 2,430	2,420 / 2,430

● Standard ● Optional – Not available

*Depending on country-specific legislative requirements and specifications

¹⁾ ECE R120 complies with ISO 14396 and 97/68EC

²⁾ With standard tyres

³⁾ Other tyres available as special equipment on request (i.e. as cost options)

You drive better when you are safe. Before using this vehicle, please read the Operating Manual and become familiar with the use of each of the controls. Note the contents of the instruction panels and use the safety equipment for your own personal safety. This brochure is intended for use internationally. The availability of a few models and of standard and special equipment items may vary from one country to another.

STEYR reserves the right at any time and without prior announcement to make changes to the design and technical version without this in any way obliging STEYR to transfer these to units already sold.

Details, descriptions and pictorial material reflect the current status at the date of publication, but can be amended without prior announcement and at any time. Pictorial materials may show certain national versions, items of special equipment as well as non-complete standard versions.

TP01 / SM / 07.21 / Printed in Austria – Cod. n. 21S0089COMINB
www.steyr-traktoren.com



steyr-traktoren.com



STEYR
TRAKTOREN